


## EPDM Lined U Bolt



### Features and Benefits

- high load capacity due to one piece design
- supplied with two or four nuts and two washers
- material: steel
- electro galvanized as per ASTM B633 Standards, BS 1706 FE/ZN 12
- noise insulating lining, EPDM, black
- designed to meet MSS Standard SP-58, type 24 and and SP-69
- special U bolts with longer tangents and threads available on request
- temperature resistance from -20°C temp to +110°C



| Part No.   | D<br>(mm) | D<br>(") | G<br>(mm) | H<br>(mm) | Lm1<br>(mm) | Fa,z<br>(N) | Pack 1 |
|------------|-----------|----------|-----------|-----------|-------------|-------------|--------|
| DMC744022L | 22        | 1/2"     | M10       | 78        | 50          | 6,000       | 300    |
| DMC744028L | 28        | 3/4"     | M10       | 84        | 50          | 6,000       | 250    |
| DMC744035L | 35        | 1"       | M10       | 90        | 50          | 6,000       | 250    |
| DMC744042L | 42        | 1 1/4"   | M10       | 98        | 50          | 6,000       | 250    |
| DMC744048L | 48        | 1 1/2"   | M10       | 106       | 50          | 6,000       | 200    |
| DMC744060L | 60        | 2"       | M10       | 115       | 50          | 6,000       | 150    |
| DMC744075L | 75        | 2 1/2"   | M12       | 133       | 50          | 10,000      | 100    |
| DMC744090L | 90        | 3"       | M12       | 146       | 50          | 10,000      | 100    |
| DMC744100L | 100       | 3 1/2"   | M12       | 156       | 50          | 10,000      | 100    |
| DMC744110L | 110       | -        | M12       | 166       | 50          | 10,000      | 100    |
| DMC744115L | 115       | 4"       | M12       | 171       | 50          | 10,000      | 70     |
| DMC744140L | 140       | 5"       | M12       | 196       | 50          | 10,000      | 60     |
| DMC744160L | 160       | -        | M12       | 214       | 50          | 10,000      | 60     |
| DMC744168L | 168       | 6"       | M12       | 220       | 50          | 10,000      | 60     |
| DMC744219L | 219       | 8"       | M16       | 301       | 50          | 10,000      | 25     |
| DMC744273L | 273       | 10"      | M20       | 379       | 100         | 32,000      | 10     |
| DMC744324L | 324       | 12"      | M20       | 430       | 100         | 32,000      | 10     |
| DMC744356L | 356       | 14"      | M20       | 462       | 100         | 32,000      | 10     |
| DMC744406L | 406       | 16"      | M20       | 512       | 100         | 32,000      | 10     |
| DMC744457L | 457       | 18"      | M24       | 563       | 100         | 45,000      | 5      |
| DMC744508L | 508       | 20"      | M24       | 614       | 100         | 45,000      | 5      |
| DMC744610L | 610       | 24"      | M24       | 715       | 100         | 45,000      | 5      |

Hot Dip Galvanized and Stainless Steel option available on request.

Alternate rod sizes for different pipe sizes are available on request (M8, M10, M12, M14, M16, M20, M24)

Measurements are subject to +/- 5% tolerance.

This series replaces part number DMC244 series.