


U-Bolt Clamps



Features and Benefits

- high load capacity due to one piece design
- supplied with nuts and washers
- material: steel
- electro galvanized as per ASTM B633 Standards, BS 1706 FE/ZN 12
- designed to meet MSS Standard SP-58, type 24 and and SP-69
- special U bolts with longer tangents and threads available on request



Part No.	D (mm)	D (")	G (mm)	H (m)	Lm 1 (mm)	Fa,z (N)	Appr.	Pack 1
DMC744028	28	3/4	M10	78	56	6,000	UL	250
DMC744035	35	1	M10	85	56	6,000	UL	250
DMC744042	42	1 1/4	M10	92	56	6,000	UL	250
DMC744048	48	1 1/2	M10	98	56	6,000	UL	200
DMC744060	60	2	M10	110	56	6,000	UL	150
DMC744075	75	2 1/2	M12	125	56	10,000	UL	100
DMC744090	90	3	M12	140	56	10,000	UL	100
DMC744115	115	4	M12	165	56	10,000	UL	70
DMC744140	140	5	M12	190	56	10,000	UL	60
DMC744168	168	6	M12	218	56	10,000	UL	60
DMC744219	219	8	M16	294	75	20,000	UL	25
DMC744273	273	10	M20	373	103	32,000	-	10
DMC744324	324	12	M20	424	103	32,000	-	10
DMC744356	356	14	M20	455	103	32,000	-	10
DMC744406	406	16	M20	505	103	32,000	-	10
DMC744457	457	18	M24	555	103	45,000	-	5
DMC744508	508	20	M24	605	103	45,000	-	5
DMC744610	610	24	M24	710	103	45,000	-	5

Hot Dip Galvanized and Stainless steel option available on request.

Sizes of the U Bolt can be modified to be used with Rubber support inserts.

Alternate rod sizes for different pipe sizes are available upon request (M8,M10,M12,M14,16,M20,M24)

Measurements are subject to +/- 5% tolerance.

This series replaces part number DMC144series.