

Heavy Duty Clevis Hanger




Type A

Type B



Features and Benefits

- design for fire fighting
- design permits vertical adjustments of pipe after installation
- hanger load nut above clevis must be tightened securely to ensure proper hanger performance
- material: steel
- designed to meet MSS Standard SP-58, type 1 and SP-69
- electrogalvanized as per ASTM B 633 Standards, BS 1706 FE/ZN 12



Part No.	D (mm)	D (")	H (mm)	d1 (mm)	Fa,z (N)	Type	Appr.	Pack 1
DMC722028	28	3/4"	69	10	4,000	A	FM,UL	200
DMC722035	35	1"	78	10	4,000	A	FM,UL	170
DMC722040	42	1 1/4 "	87	10	4,000	A	FM,UL	150
DMC722048	48	1 1/2"	101	10	4,000	A	FM,UL	100
DMC722060	60	2"	105	10	4,000	A	FM,UL	70
DMC722075	75	2 1/2"	144	10	6,500	B	FM,UL	60
DMC722090	90	3"	156	10	6,500	B	FM,UL	50
DMC722100	100	3 1/2"	180	10	6,500	B	FM,UL	50
DMC722115	115	4"	192	10	8,000	B	FM,UL	25
DMC722140	140	5"	235	12	8,000	B	FM,UL	30
DMC722168	168	6"	276	12	11,000	B	FM,UL	25
DMC722219	219	8"	345	12	13,000	B	FM,UL	20

Hot dip Galvanized and Stainless steel option available on request.
Custom made Clevis Hangers are available on requests.
Measurements are subjected to +/- 5% tolerance.
This series replaces part number ULFM Approved DMC122 series.