

Yeti®280 Roof Support System



Features and Benefits

- modular supporting system for light rooftop installations
- for horizontal and vertical applications
- flexible and cost-effective solution for pipes, cable runs, air duct channels etc.
- with non-slip anti-vibration mat
- with unique click-mechanism for quick and safe installation
- noise reduction according to DIN EN ISO 10140-1 and DIN EN ISO 10140-3
- UV-resistance according to EN ISO 16474-3:2014-02 - certified by ITB
- mouldings made of WPC, a composite of recycled plastic and wood fibre
- Part No. 67685303 consisting of:
 - 2 x BIS Yeti® 280 including non-slip anti vibration mat (made of rubber)
 - 4 x BIS Strut Connector 90°
 - 8 x hexagon head bolts and slide nuts

Part No.	Model	L (mm)	B (mm)	H (mm)	h (mm)	Fa,z (N)	Pack 1
67685280	BIS Yeti® 280 including mat	284	284	58	8	12,500	12
67685303	H-set (without Strut Rail)	284	284	58	8	12,500	1

** = Maximum allowed load for Strut 41x41x2.5.
For a detailed calculation and for support how to spread the load please contact Walraven Technical Support.
In cases where a foot is used in roof applications, the installer is obliged to verify maximum load capacity of roof before installation.*

