

## Yeti®335 Roof Support System



### Features and Benefits

- modular supporting system for HVAC equipment, solar panels, walkways, pipe work, cable runs, etc.
  - for flat roofs
  - for horizontal and vertical applications
  - 360° rotatable insert for BIS RapidStrut®
  - 41x41 or BIS RapidStrut®DS 5 (41x52mm) with non-slip anti-vibration mat
  - with unique click-mechanism for quick and safe installation
  - noise reduction according to DIN EN ISO 10140-1 and DIN EN ISO 10140-3
  - UV-resistance according to EN ISO 16474-3:2014-02 - certified by ITB
  - mouldings made of WPC, a composite of recycled plastic and wood fibre
- BIS Yeti 335 H-set consisting of:
- 2 x BIS Yeti® 335 including non-slip anti-vibration mat (made of rubber)
  - 4 x BIS Strut Connector 90°
  - 8 x hexagon head bolts and slide nuts

| Part No. | Model                      | L (mm) | B (mm) | H (mm) | h (mm) | Fa,z (N) | Fa,z 2 (N) | Ma,y (Nm) | Pack 1 | Pack 1 |
|----------|----------------------------|--------|--------|--------|--------|----------|------------|-----------|--------|--------|
| 67685201 | Vertical                   | 335    | 335    | 100    | 20     | 20,000   | 30,000     | 200.0     | 1      | 90     |
| 67685302 | H-set (without Strut Rail) | 335    | 335    | -      | 20     | 20,000   | 30,000     | 200.0     | 1      | 32     |

\* = Maximum allowed load for Strut 41x41x2.5.

\*\* = Maximum allowed load for Strut 41x51x2.0 - DS5.

For a detailed calculation and for support how to spread the load please contact Walraven Technical Support.

In cases where a foot is used in roof applications, the installer is obliged to verify maximum load capacity of roof before installation.

